



IMPIEGO

Tubo in gomma spiralato liscio idoneo per aspirazione e mandata e liquidi non corrosivi.

- **Temperatura:** -30°C +80°C



APPLICATION

Hardwall smooth cover rubber hose suitable for suction and delivery of water and non corrosive fluids.

- **Temperature range:** -30°C +80°C

STRUTTURA

- **Sottostrato:** liscio in gomma nera SBR.
- **Rinforzi:** spirale metallica incorporata con tessuti sintetici ad alta resistenza.
- **Copertura:** in gomma nera SBR/EPDM resistente all'abrasione e agli agenti atmosferici.
- **Superficie:** liscia ad impressione tela.
- **Marcatura:** listino a rilievo "H.T. - AGRIOMP/SP1OL - W.P. 10 BAR - d.i."

Disponibile su richiesta **AGRIOMP/SP1OC** con superficie esterna ondulata.

CONSTRUCTION

- **Tube:** black, smooth SBR rubber.
- **Reinforcement:** steel wire helix with high strength synthetic textile plies.
- **Cover:** black, abrasion and weathering resistant SBR/EPDM rubber.
- **Surface:** smooth fabric finished.
- **Branding:** embossed "H.T. - AGRIOMP/SP1OL - W.P. 10 BAR - d.i."

Available on request **AGRIOMP/SP1OC** with corrugated cover.

DIAMETRO INTERNO INSIDE DIAMETER		DIAMETRO ESTERNO OUTSIDE DIAMETER		PESO TEORICO WEIGHT		PRESS. ESERCIZIO WORKING PRESSURE		PRESS. SCOPPIO BURST PRESSURE		ASPIRAZ. VACUUM		RAGGIO CURVATURA BENDING RADIUS		LUNGHEZZA LENGTH
mm	inch	mm	inch	kg/mt	lbs/ft	bar	psi	bar	psi	bar	mm	inch	mt	ft
19	3/4"	29	1.5/32"	0.55	0.37	10	150	30	450	0.9	115	4.53"	40	131
25	1"	35	1.3/8"	0.77	0.52	10	150	30	450	0.9	150	5.91"	40	131
30	1.3/16"	40	1.9/16"	0.91	0.61	10	150	30	450	0.9	180	7.09"	40	131
32	1.1/4"	42	1.21/32"	0.97	0.65	10	150	30	450	0.9	190	7.48"	40	131
35	1.3/8"	45	1.3/4"	1.08	0.73	10	150	30	450	0.9	210	8.27"	40	131
38	1.1/2"	48	1.7/8"	1.20	0.81	10	150	30	450	0.9	230	9.06"	40	131
40	1.9/16"	50	1.31/32"	1.28	0.86	10	150	30	450	0.9	240	9.45"	40	131
45	1.3/4"	55	2.5/32"	1.45	0.97	10	150	30	450	0.9	270	10.06"	40	131
51	2"	62	2.7/16"	1.76	1.18	10	150	30	450	0.9	310	12.20"	40	131
60	2.3/8"	72	2.27/32"	1.80	1.21	10	150	30	450	0.9	360	14.17"	40	131
76	3"	90	3.17/32"	2.90	1.95	10	150	30	450	0.9	460	18.11"	20	65.5
80	3.5/32"	94	3.11/16"	3.20	2.15	10	150	30	450	0.9	480	18.90"	20	65.5
90	3.17/32"	106	4.3/16"	3.70	2.49	10	150	30	450	0.9	540	21.26"	20	65.5
102	4"	116	4.9/16"	4.00	2.69	10	150	30	450	0.9	610	24.02"	20	65.5
127	5"	145	5.23/32"	7.00	4.70	10	150	30	450	0.9	760	29.92"	20	65.5
152	6"	173	6.26/32"	10.00	6.72	10	150	30	450	0.9	920	36.22"	20	65.5
203	8"	228	8.31/32"	17.50	11.76	10	150	30	450	0.9	1220	48.03"	10	32.8