

POLIURETANO ANTI U.V.

Tubo spiralato singolo

Polyurethane UV-resistant
Single spiral hose

| COD. | Dimensioni Dimensions | | Tubo lineare Linear hoses | A riposo Out of work | Utilizzo Working | Spire Coils | Codoli sin - des Terminals left - right | Ø int - est ins - out |
|--------------|--------------------------|-------|------------------------------|-------------------------|---------------------|----------------|--|-----------------------------|
| | e Ø o | i Ø i | mt | mm | mt | n. | mm | mm |
| SABE8x12x4,5 | 12 | 8 | 4,5 | 300 | 3,5 | 23 | 150-150 | 50-74 |
| SABE8x12x6 | 12 | 8 | 6 | 380 | 5 | 29 | 150-150 | 50-74 |

RACCORDI DISPONIBILI - FITTINGS AVAILABLE

Femmina fisso M18x1,5
Female connection




Maschio fisso M16x1,5
Male connection



Maschio girevole M16x1,5
Male swelling connection



Molla di rinforzo
Reinforcement spring



Raccordo bicono
Swelling male with o-ring



CARATTERISTICHE - CHARACTERISTICS

Poliuretano di origine chimica con eccellente resistenza all'umidità, ottima resistenza alle basse temperature, stabilizzato alla luce e con elevata flessibilità.

Polyurethane of chemical origin with excellent humidity resistance, excellent low temperatures resistance, light stabilized. This product is very flexible.



POLIURETANO ANTI U.V.

Tubo spiralato doppio

Polyurethane UV-resistant
Double spiral hose

| COD. | Dimensioni Dimensions | | Tubo lineare Linear hoses | A riposo Out of work | Utilizzo Working | Spire Coils | Codoli sin - des Terminals left - right | Ø int - est ins - out |
|---------------|--------------------------|-------|------------------------------|-------------------------|---------------------|----------------|--|-----------------------------|
| | e Ø o | i Ø i | mt | mm | mt | n. | mm | mm |
| SE 8x12x2x4,5 | 12 | 8 | 4,5 | 300 | 3,50 | 24 | 150-150 | 50-90 |
| SE 8x12x2x6 | 12 | 8 | 6 | 380 | 5 | 29 | 150-150 | 50-90 |

COLORI DISPONIBILI - COLOURS AVAILABLE

Giallo, rosso.

Yellow, red.

