

## ELASTOLLAN® 1190 EXTRAFLEX

Spiralato con codoli dritti  
Spiral straight end hose



### CARATTERISTICHE - CHARACTERISTICS

Vedi pag. 36

At page 36

COD.	Dimensioni Dimensions		Tubo lineare Linear hoses	A riposo Out of work	Utilizzo Working	Spire Coils	Codoli sin - des Terminals left - right	Interno Inside	Esterno Outside
	e Ø o	i Ø i	mt	mm	mt	n.	mm	mm	mm
SE 2,5x4x1,5CC	4	2,5	1,5	145	1	33	100 - 100	10	18
SE 2,5x4x3CC	4	2,5	3	300	2	68	100 - 100	10	18
SE 2,5x4x4CC	4	2,5	4	210	3	50	100 - 100	20	28
SE 4x6x2CC	6	4	2	140	1,5	21	100 - 100	20	32
SE 4x6x4CC	6	4	4	325	3	47	100 - 100	20	32
SE 5,5x8x2,5CC	8	5,5	2,5	190	2	22	120 - 500	25	41
SE 5,5x8x5CC	8	5,5	5	410	4	46	120 - 500	25	41
SE 5,5x8x7,5CC	8	5,5	7,5	660	6	78	120 - 500	25	41
SE 5,5x8x10CC	8	5,5	10	800	8	94	120 - 500	25	41
SE 5,5x8x12,5CC	8	5,5	12,5	1030	10	122	120 - 500	25	41
SE 6,5x10x2,5CC	10	6,5	2,5	140	2	13	120 - 500	40	60
SE 6,5x10x5CC	10	6,5	5	330	4	30	120 - 500	40	60
SE 6,5x10x7,5CC	10	6,5	7,5	500	6	45	120 - 500	40	60
SE 6,5x10x10CC	10	6,5	10	680	8	61	120 - 500	40	60
SE 6,5x10x12,5CC	10	6,5	12,5	800	10	76	120 - 500	40	60
SE 8x12x2,5CC	12	8	2,5	115	2	9	120 - 500	50	74
SE 8x12x5CC	12	8	5	305	3	24	120 - 500	50	74
SE 8x12x7,5CC	12	8	7,5	430	6	35	120 - 500	50	74
SE 8x12x10CC	12	8	10	600	8	48	120 - 500	50	74
SE 8x12x12,5CC	12	8	12,5	800	10	63	120 - 500	50	74
SE 8x12x15CC	12	8	15	930	12	77	120 - 120	50	74

